

AMENDMENTS TO THE CLAIMS

Replace the claims with the following rewritten listing:

1. (Currently Amended) A method of conducting service on a wind turbine after the wind turbine is erected and after ~~the_a~~ hub of the wind turbine is mounted on ~~the_a~~ main shaft of the wind turbine, said method comprising ~~the steps of~~:

mounting of servicing equipment including a crane on the hub of the wind turbine, and

lowering and hoisting wind turbine appliances from and to the hub with said hub mounted servicing equipment including a crane.

2. (Currently Amended) A method according to claim 1, wherein the servicing equipment is mounted to ~~the_an~~ outside surface of the hub, and wherein appliances to be lowered from and hoisted to the hub ~~is_are~~ capable of being lowered and hoisted to the hub at a front of the hub.

3. (Currently Amended) A method according to claim 1 or claim 2, wherein the servicing equipment is mounted by means of already available holes, said holes formerly used for hoisting the hub to the main shaft of the wind turbine.

4. (Original) Equipment for servicing a wind turbine after ~~the_a~~ hub of the wind turbine has been mounted, said equipment ~~being provided with~~ comprising:

~~means for primarily securing the equipment including a crane to the hub, and~~
~~said a crane for~~ lowering and hoisting wind turbine appliances from and to the hub; and

means for primarily securing the equipment, including the crane, to the hub.

5. (Currently Amended) Equipment according to claim 4, ~~said equipment being provided with~~ further comprising fastening means, preferably bolts, for securing the equipment to already available holes, said holes formerly used for hoisting the hub to ~~the~~ a main shaft of the wind turbine.

6. (Original) Equipment according to claim 5, where the equipment is provided with a first connecting piece intended for being secured to a first set of already available holes.

7. (Currently Amended) Equipment according to claim 5 or 6, wherein the equipment is provided with a second connecting piece intended for being secured to a second set of already available holes.

8. (Currently Amended) Equipment according to claim 6 or 7, wherein the first connecting piece is intended primarily for securing a crane, constituting part of the equipment, to the hub.

9. (Currently Amended) Equipment according to any of claims 4-8~~7~~, wherein the second connecting piece is intended primarily for securing a gangway, constituting part of the equipment, to the hub.

10. (Currently Amended) Equipment according to any of claims 4-9~~6~~, wherein said connecting piece for connecting the hub with the remainder of the equipment being provided with primary holes for inserting bolts to be secured to the existing holes in the hub and thereby securing the connecting piece to the hub, and said connecting piece also being provided with secondary holes for inserting bolts for securing the remainder of the equipment to the connecting piece.

11. (Original) Equipment according to claim 10, where a cavity is formed in a bottom of the connecting piece, said cavity being intended for containing a cement-like substance when the connecting piece is secured to the hub.

12. (Original) Equipment according to claim 11, where the cavity is delimited by a collar extending circumferentially along the bottom of the connecting piece, and said collar limiting any flow from the cavity of the cement-like substance.

13. (Currently Amended) Equipment according to ~~any of the~~ claims 10–12, wherein the connecting piece, preferably the collar of the connecting piece, is provided with means for releasing ~~the~~ adherence by the cement-like structure of the connecting piece to the hub.
14. (Currently Amended) Equipment according to ~~any of the~~ claims 11–13, wherein the cavity is delimited by a disc-like member extending inside the connecting piece, and said disc-like member limiting any flow from the cavity of the cement-like substance.
15. (Currently Amended) Equipment according to ~~any of the~~ claims 10–14, wherein the connecting piece comprises a flange extending circumferentially along the connecting piece, said flange being provided with means for securing the remainder of the equipment to the connecting piece.
16. (Currently Amended) Equipment according to claim 10 and ~~claim 14~~, wherein the connecting piece is provided with an upper disc-like member and where guiding liners for bolts extend between the upper disc-like member and ~~the~~ lower disc-like members.
17. (Currently Amended) Equipment according to ~~any of the~~ claims 10–16, wherein the guiding liners are positioned relative to each other in the connecting piece corresponding to a positioning of already available holes in the hub of the wind turbine.
18. (Currently Amended) Equipment according to ~~any of the~~ claims 8–17, wherein said crane ~~being provided with~~ comprises primary holes for inserting bolts for securing the crane to the connecting piece and thus to the hub.
19. (Original) Equipment according to claim 18, where the crane is provided with a jib connected to a mast of the crane, and said jib being swivable around a substantially vertical hinged connection and said jib extending outwards in relation to the mast and

forwards in relation to a direction being a forwards direction of the wind turbine when the crane is secured to the hub.

20. (Original) Equipment according to claim 19, where links are provided between the mast and the hinged connection, said links extending outwards in relation to the mast and forwards in relation to a direction being a forwards direction of the wind turbine when the crane is secured to the hub.

21. (Original) Equipment according to claim 20, where the links have a greater dimension at an end where the links are attached to the mast and have a smaller dimension at an end where the jib by means of the hinged connection is attached to the links.

22. (Currently Amended) Equipment according to claim 20-~~or claim 21~~, wherein the links are made of a material lighter than steel.

23. (Currently Amended) Equipment according to ~~any of the claims 18-22~~, wherein the jib has an I-shaped cross section, ~~alternatively or~~ an inverted T-shaped cross-section and ~~that wherein~~ wheels of a trolley are intended for being supported on ~~the a~~ transversal parts of ~~the a~~ profile.

24. (Currently Amended) Wind turbine comprising
a hub wherein ~~the a~~ surface of said hub includes holes initially used for attaching the hub to a crane used when erecting the wind turbine, and
said holes subsequently intended for being used for securing service equipment ~~including a crane according to any of claims 4-23~~ to the surface of the hub;
wherein the service equipment comprises a crane for lowering and hoisting wind turbine appliances from and to the hub and means for primarily securing the equipment, including the crane, to the hub.

25. (Original) Wind turbine according to claim 24, wherein the surface of said hub being provided with holes initially used for attaching the hub to a crane used, when erecting the wind turbine, and said holes subsequently intended for being used for securing service equipment to the surface of the hub.

26. (Currently Amended) A method of using ~~Use~~ ~~of holes in the~~ ~~a~~ surface of a hub in a wind turbine ~~according to claim 24 and 25, said comprising:~~
~~locating~~ holes initially having been used for attaching the hub to a crane used, when erecting the wind turbine, and
~~said holes~~ ~~subsequently used~~ ~~using~~ ~~said holes~~ for securing service equipment to the surface of the hub.